


BLIND RIVETS

DOMED HEAD - MONEL STEEL

MONEL STEEL

MONEL RIVETS WITH STEEL MANDRELS

Available in Domed Head (R73MS)



RIVET CODE	RIVET DIAMETER D	HOLE SIZE (MM)	RIVET LENGTH L (MM)	GRIP RANGE G (MM)	HEAD DIAMETER H (MM)	HEAD THICKNESS T (MM)	STANDARD STRENGTH N (MIN.)	
							SHEAR	TENSILE
4-2 4-3 4-4 4-5 4-6 4-8	3.2mm	3.3 - 3.4	6.7 8.2 9.7 11.4 13.0 16.2	0.8 - 3.2 3.2 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7	6.05 - 6.65	1.02	1400	1900
5-2 5-3 5-4 5-5 5-6 5-8	4.0mm	4.1 - 4.2	7.3 8.9 10.5 12.0 13.6 16.8	0.8 - 3.2 3.2 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7	7.52 - 8.33	1.27	2200	3000
6-2 6-3 6-4 6-5 6-6 6-8 6-10 6-12	4.8mm	4.9 - 5.0	8.0 9.5 11.1 12.7 14.3 17.5 20.7 23.8	0.8 - 3.2 3.2 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7 12.7 - 15.9 15.9 - 19.1	9.04 - 10.01	1.52	3300	3700