


BLIND RIVETS

DOMED HEAD WITH LARGE FLANGE - ALUMINIUM STEEL

ALUMINIUM STEEL - LARGE FLANGE

ALUMINIUM ALLOY RIVETS WITH STEEL MANDRELS, LARGE FLANGE

Available in Domed Head Large Flange (R73ASL)



| RIVET CODE | RIVET DIAMETER D (MM) | HOLE SIZE (MM) | RIVET LENGTH L (MM) | GRIP RANGE G (MM) | HEAD DIAMETER H (MM) | HEAD THICKNESS T (MM) | STANDARD STRENGTH N (MIN.) | |
|--|-----------------------|----------------|--|---|----------------------|-----------------------|----------------------------|---------|
| | | | | | | | SHEAR | TENSILE |
| 4-2 4-3 4-4 4-5 4-6 4-8 | 3.2mm | 3.3 - 3.4 | 6.7 8.2 9.7 11.4 13.0 16.2 | 0.8 - 3.2 3.2 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7 | 9.14 - 9.91 | 1.02 | 535 | 650 |
| 5-3 5-4 5-5 5-6 5-8 5-10 | 4.0mm | 4.1 - 4.2 | 8.9 10.5 12.0 13.6 16.8 20.0 | 1.6 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7 12.7 - 15.9 | 11.4 - 12.4 | 1.27 | 850 | 1020 |
| 6-2 6-3 6-4 6-5 6-6 6-8 6-10 6-12 6-14 6-16 | 4.8mm | 4.9 - 5.0 | 8.0 9.5 11.1 12.7 14.3 17.5 20.7 23.8 27.0 30.2 | 1.6 - 3.2 3.2 - 4.8 4.8 - 6.4 6.4 - 7.9 7.9 - 9.5 9.5 - 12.7 12.7 - 15.9 15.9 - 19.1 19.1 - 22.2 22.2 - 25.4 | 15.24 - 16.51 | 1.52 | 1160 | 1420 |
| 8-4 8-6 8-8 8-10 8-12 8-14 8-16 | 6.4mm | 6.5 - 6.6 | 12.4 15.5 18.7 21.9 25.1 28.2 31.4 | 3.2 - 6.4 6.4 - 9.5 9.5 - 12.7 12.7 - 15.9 15.9 - 19.1 19.1 - 22.2 22.2 - 25.4 | 18.29 - 19.81 | 2.03 | 2050 | 2500 |