


PART OF THE NEW ZEALAND LANDSCAPE SINCE 1932




#### **BOUNDARY FENCE**

The Boundary fence is designed to handle pressure from stock with performance and exceptional value in mind. Designed for New Zealand conditions with longevity and durability, 2.5mm HT top and bottom wires and a knot that locks the vertical and horizontal wires to minimize wires sliding.

CODE	DESCRIPTION
FH89015100SK	900mm (8-90-15) Boundary Fence Square Knot Zinc/Aluminium 95/5 Roll 100m
FH89030200SK	900mm (8-90-30) Boundary Fence Square Knot Zinc/Aluminium 95/5 Roll 200m
FH88030200SK	900mm (8-90-30) Boundary Fence Square Knot Zinc/Aluminium 95/5 Roll 200m
FH88030100SK	900mm (8-90-30) Boundary Fence Square Knot Zinc/Aluminium 95/5 Roll 100m








# FARM FENCE PREMIUM STAYTIGHT

2.5mm High tensile top & bottom line wires, 2.5mm medium tensile cross wires, 2.24mm soft knot wires.

CODE	DESCRIPTION
FS89015100	Staytight HT 8-90-15 x 100m
FS89030100	Staytight HT 8-90-30 x 100m
FS88030100	Staytight HT 8-80-30 x 100m
FS67030200	Staytight HT 6-70-30 x 200m







# DEER FENCE PREMIUM STAYTIGHT

2.5mm High tensile line wires, 2.5mm medium tensile cross wires, 2.24mm soft knot wires.

CODE	DESCRIPTION
FS1319015100	Staytight HT 13-190-15 x 100m
FS1319030100	Staytight HT 13-190-30 x 100m
FS1115515100	Staytight HT 11-155-15 x 100m
FS1115530100	Staytight HT 11-155-30 x 100m







#### **CHAIN LINK NETTING**

Chain Link is New Zealand made and is suitable for all security and sports fencing applications and is available in:

- Zinc Aluminium
- Black PVC coated wire (On request)
- The size of the mesh is calculated by measuring along the side of the diamond. Mesh sizes normally used for fencing are 50mm and 75mm. Diamond sizes available are 25/50/75mm.

#### **STANDARD SPECIFICATIONS**

HEIGHT	50 X 2.5MM		75 X 2.5MM
900mm	15m	30m	30m
1000mm	30m		
1200mm	15m	30m	
1500mm	15m	30m	
1800mm	15m	30m	15m
2000mm	15m		
2400mm	15m		
2700mm	15m		

Note: Non standard specifications made to order.

#### **HEXAGONAL NETTING**

600mm


1066mm

HEX (MM)	HEIGHT (MM)	DIAMETER (MM)	LENGTH (M)		
GALVANISED HE	GALVANISED HEXAGONAL NETTING				
13mm	900mm	0.7mm	5 / 10 / 50m		
19mm	900mm	0.9mm	5/10/50m		
25mm	900mm	0.9mm	5/10/50m		
50mm	900mm	1.00mm	5 / 10 / 50m		
50mm	2000mm	1.00mm	50m		
75mm	900mm	1.00mm	50m		
75mm	2000mm	1.00mm	50m		
RABBIT NETTING					
41mm	450mm	1.4mm	50m		

1.4mm

1.4mm


## **GATE HARDWARE**





41mm

41mm




50m

50m


## **FARM GATES**

#### **ECONOMY CHAIN LINK (GFE)**




FOR STOCK	AVAILABLE IN	MATERIALS
Sheep, goats, pigs, dogs	3.05m, 3.35m, 3.66m, 4.25m, 4.88m x 1m high	Frame and bracing 25mm NB galv. pipe. Chainlink infill 75 x 2.80mm galv. Welded lugs 2 x 20mm. Lacing wire

#### **CATTLE CHAIN LINK (GFC)**



FOR STOCK	AVAILABLE IN	MATERIALS
Sheep, goats, pigs, dogs, dairy cattle, bulls, horses	3.05m, 3.66m, 4.25m x 1m high	Frame 32mm NB galv. pipe. Bracing 25mm NB galv pipe. Chainlink infill 50 x 3.15mm galv. Welded lugs. 2 x 20mm. Lacing wire 2.24mm galv.

### **DEER CHAIN LINK (GFD)**



FOR STOCK	AVAILABLE IN	MATERIALS
Sheep, goats, pigs, dogs, horses, deer	3.05m x 1.9m high, 3.66m x 1.9m high, 4.25m x 1.9m high, 3.66m x 1.55m high	Frame and bracing 25mm NB galv. pipe. Chainlink infill 75 x 2.80mm galv. Welded lugs 2 x 20mm. Lacing wire 2.24mm galv. Hand hold section.

### **BRUMBY (GFLB)**

1	<u> </u>			
		/	,	
9				


FOR STOCK	AVAILABLE IN	MATERIALS
Sheep, goats, pigs, dogs	1.85m, 2.13m, 2.44m, 2.74m, 3.05m, 3.35m, 3.66m, 3.96m, 4.25m, 4.55m, 4.88m x 1m high	Hot dip galv. frame 25mm NB pipe. Horizontal bars 5 x 6mm. 25mm flat verticals. Adjustable hinge clamps top and bottom. Diagonal support bar. Split link for catch.

#### **HEAVY BARRED (GFB)**



FOR STOCK	AVAILABLE IN	MATERIALS
Sheep, goats, pigs, dogs, horses, dairy cattle, bulls	3.05m, 3.35m, 3.66m, 3.96m, 4.25m x 1.05m high	Frame 25mm NB galv. pipe. Horizontal bars. 5 x 20mm NB galv. pipe. 2 x diagonal support bars. 1 G hook for latch. 2 zinc coated space bars. 1 x welded lug, 1 x adjustable lug.

#### **VERTICAL BARRED (GRVB)**



FOR STO	СК	AVAILABLE IN	MATERIALS
Calvin urban	g, pig sheds,	1.06m, 1.82m, 2.13m, 2.44m, 3.05m, 3.66m x 1m high	Hot dip galv. frame 25mm NB pipe. 7.5mm uprights at 100mm spacings. Adjustable hinge clamps top andbottom. Split link for latch.

#### **CHIEF (GFLCH)**


	$\overline{}$			
		$\rightarrow$		
4		_		
			$\overline{}$	بـــــــــــــــــــــــــــــــــــــ

FOR STOCK	AVAILABLE IN	MATERIALS

Sheep, goats,
pigs, dogs, horses,
dairy cattle, bulls

3.05m, 3.35m, 3.66m, 3.96m, 4.25m, 4.55m x 1.05m high Hot dip galv. frame 25mm NB pipe. Horizontal bars. 6 x 9.5mm. 25mm flat support uprights. Diagonal Support Bar. Adjustable hinge clamps top and bottom. Split link for catch.

#### **HIGHLANDER (GFLH)**



#### FOR STOCK AVAILABLE IN MATERIALS

Sheep, goats, pigs, dogs, horses, dairy cattle
3.05m, 3.35m, 3.66m, 3.96m, 4.25m x 1.05m high Hot dip galv. frame 25mm NB pipe. Horizontal bars 6 x 7.5mm. 25mm flat support uprights. Diagonal Support Bar. Adjustable hinge clamps top and bottom. Split link for catch.

### **FENCING STANDARDS**



# HI-STRENGTH FENCING STANDARDS BLACK PAINTED (Y-POST)

Commonly used in rural permanent and electric fencing applications, horticultural, tree guard and road marker posts.

The black painted coating is designed to provide reliable protection and resistance in normal environments.

CODE	DESCRIPTION	CODE	DESCRIPTION
WAR400HS	Handy Post 400mm	WAR150HS	Black Post 1500mm 7Hole
WAR500HS	Handy Post 500mm	WAR165HS	Black Post 1650mm 7Hole
WAR800HS	Handy Post 800mm	WAR1658HS	Black Post 1650mm 8Hole
WAR135HS	Black Post 1350mm 7Hole	WAR180HS	Black Post 1800mm 8Hole

Standard Bundle size 10



#### **POST DRIVER**

Ergonomic handle design allows minimum strain on the user making the driver quicker and easier to use.

CODE	DESCRIPTION
SPDRV	Fencing Standard Driver



#### **SAFETY CAP**

Designed to reduces the chance of injury to both animals and humans from exposed steel surfaces.

CODE	DESCRIPTION	PACK SIZE
WARSCAP	Fencing Standard Safety Cap	Bag 20



#### **RAPID POST**

Hurricane Rapid Post designed to speed up fencing and make installation easier, self sprung stainless steel clips holds the fencing wire in the slot – doing way with the need to cut tie wire – saving time.



FIND OUT MORE

#### WIRE



#### **FENCING WIRE REFERENCE TABLE**

CODE	DESCRIPTION	COIL SIZE KG'S SIZE KG'S	MIN. LENGTH (METRES) PER 25KG COIL
FW25HP	2.50mm High Tensile	25	650
FW25HPV	2.50mm High Tensile Vineyard	39	1,000
FW31HP	3.15mm High Tensile	25	408
FWP31SHP	3.15mm Soft (Low Tensile)	25	408
FW40HP	4.00mm Soft (Low Tensile)	25	253

 $<sup>^{\</sup>star}$  Wire Coating Specification AS/NZS 4534 W05. Nominal pack / pallet configurations: 40 of 25KG Coils Per Pallet / #10 of 39kg Coils Per Pallet.



#### **BARBED WIRE**

	CODE	WIRE SIZE	BARB SPACING	APPROX LENGTH	NOMINAL PACK WEIGHT
Standard IOWA Pattern	BWS2515025	2.5mm	75mm	240mm	25kg
	BWS257525	2.5mm	150mm	270mm	25kg
Reverse Twist Pattern	BWRT16100500	1.6mm	100mm	500mm	25kg
	BWRT16150500	1.6mm	150mm	500mm	25kg

#### LACING OF GALVANISED WIRE

LACING OF GALVANISED WIKE			
CODE	DESCRIPTION		
LN20	Needle 2.0mm x 30 metres		
GWC1610, GWC165, GWC2010, GWC205	Coiled wire 1.6mm and 2mm in 10kg and 5kg lots		

### **STAPLES**

#### **FENCING STAPLES BARBED**

Manufactured from High Performance 2 Life Zinc Aluminium wire

С	ODE	DESCRIPTION	SIZE
S	B4040T	Barbed Staple 40mm x 4.0mm x 20kg	1
S	В4040Н	Barbed Staple 40mm x 4.0mm x 5kg	4
S	B5040T	Barbed Staple 50mm x 4.0mm x 20kg	1
S	В5040Н	Barbed Staple 50mm x 4.0mm x 5kg	4







Hurricane, is recognised as a name connected with quality wire products and innovation in fencing products since 1932. We have supplied New Zealand's residential and commercial developments, infrastructure projects and rural communities for close to 90 years with hard wearing products made to last in New Zealand's harsh environment.

The first field trial of Hurricane's high tensile boundary fence was conducted in secret near Wanganui in February 1963. The resilience of this fencing and the way it could be erected on undulating ground proved to be outstanding and led to the biggest-ever success in fabricated farm-fence development in New Zealand. The later introduction of Hurricane deer fence established New Zealand as an exporter of market leading innovative fencing-systems.

### **BUILT TO LAST**

Our proven range of product includes:

- Fencing wire
- Farm fence
- Rural gates
- Gate fittings
- Fencing standards
- Fencing panels
- Chain link panels
- Nails and staples
- Reinforcing products; mesh, tie wire, rebar and bar chairs









The 'Hurricane Rural Product Guide' is provided for reference only without any guarantees or warranty, and subject to change without notification. In association with the 'Hurricane Rural Product Guide', Steel & Tube Holdings Ltd. makes no warranties of any kind, either express or implied, including but not limited to warranties of merchantability, fitness for a particular purpose, of title, without infringement of third party rights. Use of this publication, these products and the information contained within by a user is at the user's risk, to check it's accuracy for their own purposes. In no case shall the information provided be considered a part of our terms and conditions of sale.

FIND OUT MORE

0800 478 335 steelandtube.co.nz