


SEVEN SUCCESSFUL STEPS TO GATE HANGING

- 1 Standing at the strainer post, looking down the fence line, draw a line through the centre of the strainer post.
- 2 Then another line at a 90° angle to this.
- 3 Draw a bisecting line between to form a 45° angle – this will be the angle the gudgeons will be placed at.
- 4 From this line run a spirit level or vertical plumb line down the post.
- 5 Place the gate against the post and mark off underneath each lug of the gate at the desired height (taking into consideration the ground clearance under the gate and the height of the post).
- 6 Use the cross formed by the gate lug height and vertical plumb line as a reference point. For larger post sizes, the hole may need to be further from the reference point, ie: closer to the fence to ensure the gate can open flat against the fence, avoiding gate binding. This stops stock being trapped behind the gate and prolongs the life of both gate and gudgeon.
- 7 Drill the bottom hole first, boring into the post horizontally in line with the 45° line. Locate the gudgeon half way into the post hole. Then use this gudgeon for a reference when drilling the top hole – make sure it is parallel to the bottom one.



The Hurricane range includes:

- › Gates
- › Gate Fittings
- › Fencing Wire
- › Fence Posts
- › Deer Fence
- › Home Fence
- › School Fence
- › Security Panel Fence
- › Chain Link
- › Staples & Barbed Wire

To find out more about our extensive Steel & Tube range of products and services:

- › Steel
- › Pipe, Fittings & Valves
- › Stainless Steel
- › Fastenings
- › Chain & Rigging
- › Rural Products
- › Industrial Products
- › Reinforcing
- › Roofing, Cladding, Rainwater Systems & Purlins

CONTACT US TODAY:

0800 478 335

www.steelandtube.co.nz



STRONGER IN EVERYWAY



PRODUCT GUIDE
GATES



PRODUCT GUIDE › GATES


MAY 2018

RURAL & FENCING

For over 80 years Hurricane has provided a range of high quality, hard wearing products made to last in New Zealand's harsh environment.




BRUMBY




FOR STOCK	Sheep, goats, pigs, dogs
AVAILABLE IN	2.44m, 3.05m, 3.66m, 3.96m, 4.25m, 4.55m, 4.88m x 1m high
MATERIALS	Hot dip galv. frame 25mm NB pipe. Horizontal bars 5 x 6mm. 25mm flat verticals. Adjustable hinge clamps top and bottom. Diagonal support bar. Split link for catch.

DEER




FOR STOCK	Sheep, goats, pigs, dogs, horses, deer
AVAILABLE IN	3.05m x 1.9m high, 3.66m x 1.9m high, 4.25m x 1.9m high, 3.66m x 1.55m high
MATERIALS	Frame and bracing 25mm NB galv. pipe. Chainlink infill 75 x 2.80mm galv. Welded lugs 2 x 20mm. Lacing wire 2.24mm galv. Hand hold section.

ECONOMY




FOR STOCK	Sheep, goats, pigs, dogs
AVAILABLE IN	3.05m, 3.35m, 3.66m, 4.25m, 4.88m x 1m high
MATERIALS	Frame and bracing 25mm NB galv. pipe. Chainlink infill 75 x 2.80mm galv. Welded lugs 2 x 20mm. Lacing wire 2.24mm galv.

HEAVY BARRED




FOR STOCK	Sheep, goats, pigs, dogs, horses, dairy cattle, bulls
AVAILABLE IN	3.05m, 3.66m, 3.96m, 4.25m x 1.05m high
MATERIALS	Frame 25mm NB galv. pipe. Horizontal bars 5 x 20mm NB galv. pipe. 2 x diagonal support bars. 1 G hook for latch. 2 zinc coated space bars. 1 x welded lug, 1 x adjustable lug.

VERTICAL BARRED




FOR STOCK	Calving, pig sheds, urban
AVAILABLE IN	1.06m, 1.82m, 2.13m, 3.05m, 3.66m x 1m high
MATERIALS	Hot dip galv. frame 25mm NB pipe. 7.5mm uprights at 100mm spacings. Adjustable hinge clamps top and bottom. Split link for latch.

CHIEF




FOR STOCK	Sheep, goats, pigs, dogs, horses, dairy cattle, bulls
AVAILABLE IN	3.66m, 4.25m x 1.05m high
MATERIALS	Hot dip galv. frame 25mm NB pipe. Horizontal bars 6 x 9.5mm. 25mm flat support uprights. Diagonal Support Bar. Adjustable hinge clamps top and bottom. Split link for catch.

CATTLE



FOR STOCK	Sheep, goats, pigs, dogs, dairy cattle, bulls, horses
AVAILABLE IN	3.05m, 3.66m, 4.25m x 1m high
MATERIALS	Frame 32mm NB galv. pipe. Bracing 25mm NB galv. pipe. Chainlink infill 50 x 3.15mm galv. Welded lugs 2 x 20mm. Lacing wire 2.24mm galv.

HIGHLANDER



FOR STOCK	Sheep, goats, pigs, dogs, horses, dairy cattle
AVAILABLE IN	3.05m, 3.66m, 3.96m, 4.25m x 1.05m high
MATERIALS	Hot dip galv. frame 25mm NB pipe. Horizontal bars 6 x 7.5mm. 25mm flat support uprights. Diagonal Support Bar. Adjustable hinge clamps top and bottom. Split link for catch.